



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/719,771	11/21/2003	Richard D. Ellison	200308979-1	3099

22879 7590 06/05/2007  
HEWLETT PACKARD COMPANY  
P O BOX 272400, 3404 E. HARMONY ROAD  
INTELLECTUAL PROPERTY ADMINISTRATION  
FORT COLLINS, CO 80527-2400

EXAMINER
----------

SWERDLOW, DANIEL

ART UNIT	PAPER NUMBER
----------	--------------

2615

MAIL DATE	DELIVERY MODE
-----------	---------------

06/05/2007

PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

# Office Action Summary

Application No.

10/719,771

Applicant(s)

ELLISON, RICHARD D.

Examiner

Daniel Swerdlow

Art Unit

2615

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

## Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

## Status

- 1)  Responsive to communication(s) filed on 04 May 2007.
- 2a)  This action is **FINAL**.                      2b)  This action is non-final.
- 3)  Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

## Disposition of Claims

- 4)  Claim(s) 1-37 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5)  Claim(s) \_\_\_\_\_ is/are allowed.
- 6)  Claim(s) 1-37 is/are rejected.
- 7)  Claim(s) \_\_\_\_\_ is/are objected to.
- 8)  Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

## Application Papers

- 9)  The specification is objected to by the Examiner.
- 10)  The drawing(s) filed on \_\_\_\_\_ is/are: a)  accepted or b)  objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11)  The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

## Priority under 35 U.S.C. § 119

- 12)  Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a)  All    b)  Some \* c)  None of:
- Certified copies of the priority documents have been received.
  - Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  - Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

## Attachment(s)

- |  |   |
|--|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892)   | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)                       | 5) <input type="checkbox"/> Notice of Informal Patent Application                       |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)<br>Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____  |

## DETAILED ACTION

### *Claim Rejections - 35 USC § 102*

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

2. Claims 1 through 37 are rejected under 35 U.S.C. 102(b) as being anticipated by Smith et al. (US Patent 5,267,322).

3. Regarding Claim 1, Smith discloses an automatic gain control comprising: signal level measurement (i.e., a module to measure power level) (Fig. 3, step 312; column 11, lines 9-23) for a stream of frames representing voice signals for conversion to audible signals (i.e., outgoing voice signal stream) (column 7, lines 58-69; column 8, lines 38-42) in a DSP (Fig. 1C, reference 21); gain value adjustment (i.e., a gain factor setting module) (Fig. 3, steps 326, 330; column 12, lines 38-63) that sets gain by comparing signal level to thresholds (Fig. 3, steps 326,330); and application of gain (i.e., a gain adjustment module) (Fig. 3, steps 328, 332, 334, 336; column 12, lines 38-63) by applying the gain value to maintain a preferred desired average output level on the telephone line (i.e., to operate within compliance of a PSTN (column 14, lines 1-3). Further, Smith discloses the measuring and adjustment occurring in a DSP (Fig. 1C, reference 21; Fig. 3, step 312; column 11, lines 9-23; Fig. 3, steps 328, 332, 334, 336; column 12, lines 38-63) before output on a transmit frame on the TDM highway to a digital to analog converter on a LIM (Fig. 1A, reference 24) for conversion to an audible signal (column 8, lines 62-65) that is output on a

Art Unit: 2615

public switched telephone line (Fig. 1A, reference 70; column 5, lines 27-29) that corresponds to the output channel claimed and is in communication with the PSTN (column 1, lines 25-29).

4. Regarding Claim 2, Smith further discloses use of two thresholds (Fig. 3, steps 326, 380; column 12, lines 38-63).

5. Regarding Claim 3, Smith further discloses simultaneous use of signal level values for current and future subframes (Fig. 3, step 312; column 11, lines 9-11). The simultaneous use of signal level values from different times inherently includes storing measured levels. In addition, Smith discloses the use of a program variable representing a gain value (i.e., storing a previously applied gain value) (column 12, lines 41-44).

6. Regarding Claim 4, Smith further discloses applying gain values to maintain a level between a low threshold and a high threshold (column 12, lines 38-63).

7. Regarding Claim 5, Smith further discloses multiplying the gain value to the current signal value (column 11, lines 41-44).

8. Regarding Claim 6, Smith further discloses applying (i.e., adding) the gain value to the current signal value (column 11, lines 41-44).

9. Regarding Claim 7, in addition to the elements cited above apropos of Claim 1, Smith further discloses a TDM interface (Fig. 1B, reference 63; column 6, lines 3-7) the corresponds to the switch claimed and assigns serial bit blocks (i.e., receives a voice signal stream) from the TDM interface (i.e., a voice signal source) to one of the APU's that includes the gain control function that corresponds to the gain adjustment module claimed. In addition, Smith further discloses measuring signal level at two future and one current subframe (i.e., a number of segments) (column 11, lines 9-11). Further, Smith discloses outputting stream of frames

Art Unit: 2615

representing voice signals for conversion to audible signals (i.e., the voice signal stream is outgoing) (column 8, lines 38-42). Further, Smith discloses the measuring and adjustment occurring in a DSP (Fig. 1C, reference 21; Fig. 3, step 312; column 11, lines 9-23; Fig. 3, steps 328, 332, 334, 336; column 12, lines 38-63) before output on a transmit frame on the TDM highway to a digital to analog converter on a LIM (Fig. 1A, reference 24) for conversion to an audible signal (column 8, lines 62-65) that is output on a public switched telephone line (Fig. 1A, reference 70; column 5, lines 27-29) that corresponds to the output channel claimed.

10. Regarding Claim 8, Smith further discloses sending a gain adjusted frame as a transmit frame on the TDM highway (i.e., adjusting gain before the signal has entered an output channel) (column 8, lines 62-65).

11. Regarding Claim 9, Smith further discloses simultaneous use of signal level values for current and future subframes (Fig. 3, step 312; column 11, lines 9-11). The simultaneous use of signal level values from different times inherently includes storing measured levels.

12. Regarding Claim 10, Smith further discloses taking the sum of the values of the points in the subframes (column 11, lines 13-16).

13. Regarding Claim 11, Smith further discloses computing the mean of the values of the points in the subframes (column 11, lines 10-12).

14. Regarding Claim 12, Smith further discloses applying gain values to maintain a level below a high threshold (column 12, lines 38-63). In addition, Smith further discloses a table of signal level values and associated gain values, each signal level value corresponding to one of the at least two different high threshold levels claimed (Fig. 6, reference 600; column 12, lines 54-62).

Art Unit: 2615

15. Regarding Claim 13, Smith further discloses applying gain values to maintain a level between a low threshold and a high threshold (column 12, lines 38-63).

16. Regarding Claim 14, Smith discloses a gain control system comprising: line interfaces (column 3, line 66 through column 4, line 2) that correspond to the voice signal source claimed and provide digital voice data (i.e., produces a voice signal stream) and are coupled to the public switched network (column 5, lines 27-29); Smith further discloses a voice messaging system (Fig. 1A, reference 1; column 5, lines 5-7) that corresponds to the media platform claimed and is coupled to the public switched network (column 5, lines 27-29) and the line interfaces (column 3, line 66 through column 4, line 2) that correspond to the voice signal source claimed. Smith further discloses: a TDM interface (Fig. 1B, reference 63; column 6, lines 3-7) that corresponds to the switch claimed and assigns serial bit blocks (i.e., receives a voice signal stream) from the TDM interface (i.e., a voice signal source); an automatic gain control (Fig. 2A, reference 110; column 5, lines 5-7) that corresponds to the power level adjusting means claimed to maintain a preferred desired average output level on the telephone line (i.e., to operate within compliance of a PSTN (column 14, lines 1-3); and line interface modules (Fig. 1A, reference 24,26; column 5, lines 27-39) that correspond to the output channel claimed. Further, Smith discloses outputting stream of frames representing voice signals for conversion to audible signals (i.e., the voice signal stream is outgoing) (column 8, lines 38-42). Further, Smith discloses the measuring and adjustment occurring in a DSP (Fig. 1C, reference 21; Fig. 3, step 312; column 11, lines 9-23; Fig. 3, steps 328, 332, 334, 336; column 12, lines 38-63) before output on a transmit frame on the TDM highway to a digital to analog converter on a LIM (Fig. 1A, reference 24) for conversion to an audible signal (column 8, lines 62-65) that is output on a public switched

Art Unit: 2615

telephone line (Fig. 1A, reference 70; column 5, lines 27-29) that corresponds to the output channel claimed.

17. Regarding Claim 15, Smith further discloses the gain control implemented in assembly code software on a DSP (i.e., having a set of computer executable instructions) (column 6, lines 35-37).

18. Regarding Claim 16, Smith further discloses signal level measurement (i.e., measurement module) (Fig. 3, step 312; column 11, lines 9-23); gain value adjustment (i.e., a gain factor setting module) (Fig. 3, steps 326, 330; column 12, lines 38-63) that sets gain by comparing signal level to thresholds (Fig. 3, steps 326,330); and application of gain (i.e., a gain adjustment module) (Fig. 3, steps 328, 332, 334, 336; column 12, lines 38-63) by applying the gain value.

19. Regarding Claim 17, Smith further discloses the signal level measurement that corresponds to the measurement module claimed measuring signal (i.e., power) level (Fig. 3, step 312; column 11, lines 9-23) for a stream of frames representing voice signals (i.e., voice signal stream) (column 7, lines 58-69).

20. Regarding Claim 18, Smith further discloses the gain value adjustment that corresponds to the gain factor setting module claimed (Fig. 3, steps 326, 330; column 12, lines 38-63) sets gain by comparing signal level to thresholds (i.e., based on measurement information from the measurement module (Fig. 3, steps 326,330)).

21. Regarding Claim 19, Smith further discloses the application of gain that corresponds to the gain adjustment module claimed (Fig. 3, steps 328, 332, 334, 336; column 12, lines 38-63) applying the gain value based on the gain value adjustment that corresponds to the gain factor setting module claimed (Fig. 3, steps 326, 330; column 12, lines 38-63).

Art Unit: 2615

22. Regarding Claim 20, Smith further discloses the gain control implemented in assembly code software on a DSP (i.e., including program instructions executed on a processor) (column 6, lines 35-37) within the voice messaging system that corresponds to the media platform claimed (Fig. 1C, reference 72; column 7, lines 61-64).

23. Regarding Claim 21, Smith discloses an automatic gain control (i.e., method of adjusting power level) comprising: receiving a stream of frames representing voice signals (i.e., voice signal stream) (column 7, lines 58-69); signal level measurement (i.e., measuring a power level) (Fig. 3, step 312; column 11, lines 9-23) for current and future subframes (i.e., at a number of points in time) (Fig. 3, step 312; column 11, lines 9-11); comparing signal level to thresholds (Fig. 3, steps 326,330); and application of gain (i.e., adjusting power level) (Fig. 3, steps 328, 332, 334, 336; column 12, lines 38-63) by applying a gain value based on the comparison (Fig. 3, steps 326, 330; column 12, lines 38-63) to maintain a preferred desired average output level on the telephone line (i.e., to operate within compliance of a PSTN (column 14, lines 1-3). Further, Smith discloses outputting stream of frames representing voice signals for conversion to audible signals (i.e., the voice signal stream is outgoing) (column 8, lines 38-42). Further, Smith discloses the measuring and adjustment occurring in a DSP (Fig. 1C, reference 21; Fig. 3, step 312; column 11, lines 9-23; Fig. 3, steps 328, 332, 334, 336; column 12, lines 38-63) before output on a transmit frame on the TDM highway to a digital to analog converter on a LIM (Fig. 1A, reference 24) for conversion to an audible signal (column 8, lines 62-65) that is output on a public switched telephone line (Fig. 1A, reference 70; column 5, lines 27-29) that corresponds to the output channel claimed.



Art Unit: 2615

24. Regarding Claim 22, Smith further discloses use of two thresholds (Fig. 3, steps 326, 380; column 12, lines 38-63).

25. Regarding Claim 23, Smith further discloses adjusting power level (Fig. 3, steps 328, 332, 334, 336; column 12, lines 38-63) by applying a gain value based on the comparison (Fig. 3, steps 326, 330; column 12, lines 38-63).

26. Regarding Claim 24, Smith further discloses signal level measurement (i.e., measuring a power level) (Fig. 3, step 312; column 11, lines 9-23) for current and future subframes (i.e., segments) (Fig. 3, step 312; column 11, lines 9-11).

27. Regarding Claim 25, Smith further discloses reducing gain only if signal level measurement (i.e., measuring a power level) (Fig. 3, step 312; column 11, lines 9-23) for all three subframes (i.e., segments) (Fig. 3, step 312; column 11, lines 9-11) are below a threshold. As such, Smith discloses comparing the level of each segment with the threshold.

28. Regarding Claim 26, Smith further discloses using the mean (i.e., average) of the values of the points in the subframes (column 11, lines 10-12).

29. Regarding Claim 27, in addition to the elements cited above apropos of Claim 21, Smith further discloses maintaining instructions for the method on disk drives (i.e., a computer readable medium) (column 7, lines 36-39).

30. Regarding Claim 28, Smith further discloses a table of signal level values and associated gain values (i.e., adjusting power level in differing increments based on proximity of measured power to threshold) (Fig. 6, reference 600; column 12, lines 54-62).

31. Regarding Claim 29, Smith further discloses using the mean (i.e., average) of the values of the points in the subframes (column 11, lines 10-12).

Art Unit: 2615

32. Regarding Claim 30, Smith further discloses use of signal level values for current and future subframes (i.e., replacement of oldest value with new value) (Fig. 3, step 312; column 11, lines 9-11).

33. Regarding Claim 31, Smith further discloses interface with a T1 channel (Fig. 1A, reference 26; column 5, lines 33-39).

34. Regarding Claim 32, Smith further discloses the voice data stream stored in memory (Fig. 2A, reference 100; column 12, lines 38-42).

35. Regarding Claim 33, Smith further discloses a text-to-speech application (column 7, lines 21-25).

36. Regarding Claim 34, Smith discloses an automatic gain control (i.e., method of adjusting power level) comprising: receiving a stream of frames representing voice signals (i.e., voice signal stream) (column 7, lines 58-69); signal level measurement (i.e., measuring a power level) (Fig. 3, step 312; column 11, lines 9-23) for current and future subframes (i.e., at a number of points in time) (Fig. 3, step 312; column 11, lines 9-11); comparing signal level to thresholds (Fig. 3, steps 326,330); and application of gain (i.e., adjusting power level) (Fig. 3, steps 328, 332, 334, 336; column 12, lines 38-63) by applying a gain value based on the comparison (Fig. 3, steps 326, 330; column 12, lines 38-63) over a period of time (i.e., gradually) (column 12, lines 45-49) to maintain a preferred desired average output level on the telephone line (i.e., to operate within compliance of a PSTN (column 14, lines 1-3). Further, Smith discloses outputting stream of frames representing voice signals for conversion to audible signals (i.e., the voice signal stream is outgoing) (column 8, lines 38-42). Further, Smith discloses the measuring and adjustment occurring in a DSP (Fig. 1C, reference 21; Fig. 3, step 312; column 11, lines 9-23;

Art Unit: 2615

Fig. 3, steps 328, 332, 334, 336; column 12, lines 38-63) before output on a transmit frame on the TDM highway to a digital to analog converter on a LIM (Fig. 1A, reference 24) for conversion to an audible signal (column 8, lines 62-65) that is output on a public switched telephone line (Fig. 1A, reference 70; column 5, lines 27-29) that corresponds to the output channel claimed.

37. Regarding Claim 35, Smith further discloses a table of signal level values and associated gain values (i.e., changing an amount of adjustment based on proximity of measured power to target) (Fig. 6, reference 600; column 12, lines 54-62).

38. Regarding Claim 36, Smith further discloses a table of at least four signal level values and associated gain values (i.e., comparing power levels to four thresholds) (Fig. 6, reference 600; column 12, lines 54-62).

39. Regarding Claim 37, Smith further discloses maintaining a target output level (column 14, lines 1-3). As such, Smith discloses a larger adjustment for values further from the target.

### ***Response to Arguments***

40. Applicant's arguments filed 4 May 2007 have been fully considered but they are not persuasive.

41. Applicant alleges that the prior art fails to disclose an output channel that is communicating the outgoing voice signal stream to a Public Switched Telephone Network and applying the gain value before the outgoing voice signal stream enters the output channel in communication with the PSTN, as claimed in the independent claims. Examiner respectfully disagrees. As applicant admits, Smith discloses connection to a central office switch on a public

Art Unit: 2615

switched telephone line. Whether there is a private telephone system connected to the PSTN line for the purpose, for example, of providing an enterprise with external communications is irrelevant since the signals transmitted from the private system to the PSTN are subject to the gain control disclosed before being sent in order to conform to a preferred desired average output level of -12 dBm RMS at the tip-ring interface of a telephone line (column 14, lines 1-3). It is well known that the tip-ring interface refers to the two-wire standard analog interface to the PSTN. As such, it is clear that Smith discloses applying a gain value before an outgoing voice signal stream enters an output channel in communication with the PSTN.

### *Conclusion*

42. Applicant's amendment necessitated any new grounds of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire **THREE MONTHS** from the mailing date of this action. In the event a first reply is filed within **TWO MONTHS** of the mailing date of this final action and the advisory action is not mailed until after the end of the **THREE-MONTH** shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than **SIX MONTHS** from the date of this final action.

Art Unit: 2615

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Daniel Swerdlow whose telephone number is 571-272-7531. The examiner can normally be reached on Monday through Friday between 7:30 AM and 5:00 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Sinh H. Tran can be reached on 571-272-7564. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.



Daniel Swerdlow  
Primary Examiner  
Art Unit 2615

ds  
31 May 2007